

heat-resistant expansive members from inorg. fibers and)

L1 ANSWER 12 OF 72 CA COPYRIGHT 2004 ACS on STN
AN 119:98096 CA
ED Entered STN: 04 Sep 1993
TI Fire-resistant heat-insulating coating materials
IN Karita, Reiji
PA Japan
SO Jpn. Kokai Tokkyo Koho, 3 pp.
CODEN: JKXXAF
DT Patent
LA Japanese
IC ICM C09D005-18
CC 42-10 (Coatings, Inks, and Related Products)
FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 05043822	A2	19930223	JP 1991-288231	19910813
PRAI	JP 1991-288231		19910813		

AB The title comps. contain polymeric film-forming components and .gtoreq.5% (based solids) unexpanded powder of expandable minerals such as vermiculite, perlite, etc. A compn. from **unexpanded vermiculite** powder 100, clay 15, and 20%-solids poly(vinyl acetate) emulsion 40 parts was coated on an iron plate and dried at room temp.

ST fire resistant heat insulating coating

IT Perlite

RL: USES (Uses)

wt %	pbw	
65%	100	unexpanded vermiculite
10%	15	clay
25%	40	polyvinylacetate emulsion
100 %	155	total pts

Claims 1, 5, 6, 9, 10, 13, 16, 17, 18, 19, 23, 24,
26, 27, 34, 40, 42, 43, 46, 51, 52, 53
54, 62, 67, 72, 73, 74-77